



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/737,118	12/17/2003	Yasuhiko Matsunaga	U2054.0147	6044

32172 7590 04/18/2007

DICKSTEIN SHAPIRO LLP
1177 AVENUE OF THE AMERICAS (6TH AVENUE)
NEW YORK, NY 10036-2714

EXAMINER

MILORD, MARCEAU

ART UNIT	PAPER NUMBER
----------	--------------

2618

SHORTENED STATUTORY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE
3 MONTHS	04/18/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

Office Action Summary	Application No. 10/737,118	Applicant(s) MATSUNAGA, YASUHIKO	
	Examiner Marceau Milord	Art Unit 2618	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 17 December 2003.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-46 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1,2,4,5,7-11,14,17-23,26-29 and 31-46 is/are rejected.
- 7) ☒ Claim(s) 3,6,12,13,15,16,24,25 and 30 is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Claim Objections

1. Claim 37 is objected to because of the following informalities: In claim 37, page 12, line 7, "radio base station ", should be deleted. Appropriate correction is required.

Claim Rejections - 35 USC § 103

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 1-2, 4-5, 7-11, 14, 17-23, 26-29, 33-37, 41-43, 46 are rejected under 35 U.S.C. 103(a) as being unpatentable over Takao et al (US Patent No 6871071 B2) in view of Sawahashi et al (US Patent No 5590409) and Carlsson et al (US Patent No 6167240).

Regarding claims 1-2, Takao et al discloses a radio resource management method (figs. 1-3) comprising the control steps of: detecting (32 or 31 of figs. 1 and 6) the occurrence of

Art Unit: 2618

interference between service areas provided by plural radio base stations (21 or 22 of fig. 1 and fig. 6; col. 3, line 44- col. 4, line 16; col. 7, line 59-col. 8, line 33) and controlling (RNC of figs. 1 and 6) transmission power of a common control signal, which governs a scope of a service area that a radio base station forms for interference suppression (col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of controlling transmission power of a common control signal, which governs a scope of a service area that a radio base station forms, for interference suppression in response to said occurrence of interference between service areas provided by plural radio base stations; detecting the occurrence of interference based on radio link quality information notified from each of said radio base stations.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service

Art Unit: 2618

area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Art Unit: 2618

Regarding claims 4-5, Takao et al discloses a radio resource apparatus (figs. 1-3) comprising: detecting (32 or 31 of figs. 1 and 6) the occurrence of interference between service areas provided by plural radio base stations (21 or 22 of fig. 1 and fig. 6; col. 3, line 44- col. 4, line 16; col. 7, line 59-col. 8, line 33) and controller for controlling (RNC of figs. 1 and 6) transmission power of a radio base station (21 and 22 of figs. 1 and 6; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of controlling transmission power of a common control signal which governs a scope of a service area that a radio base station forms for interference suppression in response to said occurrence of interference between service areas provided by plural radio base stations; wherein the occurrence of interference is detecting based on radio link quality information notified from each of said radio base stations.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service

Art Unit: 2618

area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claims 7-10, Takao et al discloses a radio base station in a radio communication system (figs. 1, 3, 6), said radio communication system including plural radio base stations each which provides a service area and a radio resource management apparatus for managing radio resources of said radio base stations (21 or 22 of fig. 1 and fig. 6; col. 3, line 44- col. 4, line 16; col. 7, line 59- col. 8, line 33), comprising: means (32 or 31 of figs. 1 and 6) for measuring a radio link quality and then notifying a radio resource management apparatus of radio link quality information being a measurement result (col. 9, line 42- col. 10, line 55; col. 11, lines 4- 65; col. 13, lines 45- col. 14, line 29; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the features of a means for responding transmission power control issued from a radio resource management apparatus and then controllably changing transmission power, of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference between service areas detected based on said measurement result in said radio resource management apparatus; wherein said notification means performs a notification operation at predetermined notification intervals; wherein when said radio link quality exceeds a predetermined threshold value, said notification interval is set longer than said threshold value, wherein when a distribution value of a radio link quality measured within a fixed period exceeds a predetermined threshold value, said notification interval is set longer than said threshold value.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station

Art Unit: 2618

measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile

Art Unit: 2618

stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claim 11, Takao et al discloses a radio resource management method (figs. 1-3) comprising the steps of: detecting (32 or 31 of figs. 1 and 6) the occurrence of interference between service areas provided by plural radio base stations (21 or 22 of fig. 1 and fig. 6; col. 3, line 44- col. 4, line 16; col. 7, line 59- col. 8, line 33) and controlling (RNC of figs. 1 and 6) transmission power (col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of controlling transmission power of a common control signal, which governs a scope of a service area that a radio base station forms, for interference suppression in response to said occurrence of interference between service areas provided by plural radio base stations; detecting the occurrence of interference based on radio link quality information notified from each of said radio base stations.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station

measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile

Art Unit: 2618

stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claim 14, Takao et al discloses a radio base station (figs. 1, 3, 6; 21 or 22 of figs. 1, 3, 6), comprising a detector for detecting (32 or 31 of figs. 1 and 6) the occurrence of interference between service areas provided by plural radio base stations (21 or 22 of fig. 1 and fig. 6; col. 3, line 44- col. 4, line 16; col. 7, line 59- col. 8, line 33) and controller for controlling (RNC of figs. 1 and 6) transmission power (21 and 22 of figs. 1 and 6; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of controlling transmission power of a common control signal which governs a scope of a service area that a radio base station forms, to suppress interference autonomously in response to said occurrence of interference between plural service areas.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In

Art Unit: 2618

addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line

Art Unit: 2618

11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claims 17-19, Takao et al discloses a radio resource method (figs. 1-3; 12 of figs. 1 and 3) comprising the steps of: receiving information of radio link qualities from plural radio terminals (32 or 31 of figs. 1 and 6; col. 3, line 44- col. 4, line 16; col. 7, line 59-col. 8, line 33) and controlling (RNC of figs. 1 and 6) a load, being a radio terminal accommodated in a radio base station (21 and 22 of figs. 1 and 6; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of controlling a load, based on the information of radio link qualities from plural radio terminals, where the radio link quality information including radio interference information.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference

Art Unit: 2618

signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line

Art Unit: 2618

11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claims 20-22, Takao et al discloses a radio resource method (figs. 1-3; 12 of figs. 1 and 3) comprising: a receiver for receiving information of radio link qualities from plural radio terminals (32 or 31 of figs. 1 and 6; col. 3, line 44- col. 4, line 16; col. 7, line 59-col. 8, line 33) and a controller for distributively controlling (RNC of figs. 1 and 6) a load accommodated in a radio base station (21 and 22 of figs. 1 and 6; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of controlling a load, based on the information of radio link qualities from plural radio terminals, wherein the radio link quality information includes information on link utilization to a radio base station, which is in communication with each of the radio terminals.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal

Art Unit: 2618

power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the

Art Unit: 2618

invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claim 23, Takao et al discloses a radio resource management method (figs. 1-3; 12 of figs. 1 and 3) comprising the steps of receiving information of radio link qualities from plural radio terminals (32 or 31 of figs. 1 and 6; col. 3, line 44- col. 4, line 16; col. 7, line 59-col. 8, line 33) and a controller for controlling power (RNC of figs. 1 and 6) of a radio base station (21 and 22 of figs. 1 and 6; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of controlling transmission power of a radio bases station based on the information of radio link qualities from plural radio terminals.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of

Art Unit: 2618

controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and

Art Unit: 2618

Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claims 26-28, Takao et al discloses a radio resource management apparatus (figs. 1-3; 12 of figs. 1 and 3) comprising: a receiver for receiving information of radio link qualities from plural radio terminals (32 or 31 of figs. 1 and 6; col. 3, line 44- col. 4, line 16; col. 7, line 59-col. 8, line 33) and controller for controlling (RNC of figs. 1 and 6) transmission power of a radio base station (21 and 22 of figs. 1 and 6; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of controlling transmission power of a radio base station based on the information of radio link qualities from plural radio base stations.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service

Art Unit: 2618

area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Art Unit: 2618

Regarding claim 29, Takao et al discloses a radio resource management method (figs. 1-3; 12 of figs. 1 and 3) comprising the steps of: receiving information of radio link qualities from plural radio terminals (32 or 31 of figs. 1 and 6; col. 3, line 44- col. 4, line 16; col. 7, line 59-col. 8, line 33) and controlling (RNC of figs. 1 and 6) changing a frequency used by a radio base station (21 and 22 of figs. 1 and 6; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the features of controllably changing a frequency used by a radio base station based on the information of radio link qualities from plural radio terminals.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claims 33-36, Takao et al discloses a radio terminal (figs. 1-3; 32 or 31 of figs. 1 and 3) comprising: means (21 or 22 of figs. 1 and 3) for measuring a radio link quality and then

Art Unit: 2618

notifying a radio resource management apparatus (12 of figs. 1 and 3) of radio link quality information being the measurement result (col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the features of a radio interference information; and a means for responding distributed control indication for a load being a radio terminal accommodated in a radio base station, based on said radio link quality information, wherein said notifying means performs a notifying operation at predetermined notification intervals, wherein when a radio link quality exceeds a predetermined threshold value, said notification interval is set longer than that in the case of less than said threshold value, wherein when a distribution value of a radio link quality measured within a fixed period exceeds a predetermined threshold value, said notification interval is set longer than that in the case of less than said threshold value.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of

Art Unit: 2618

controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and

Art Unit: 2618

Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claim 37, Takao et al discloses a computer readable program (figs. 1-3), that operably controls a radio resource management apparatus (12 of figs. 1 and 3) in a radio communication system (col. 3, line 44- col. 4, line 16; col. 8, line 33; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of responding to occurrence of interference between service areas provided by plural radio base station and then controlling the transmission power of a common control signal, which governs a scope of service area that a radio base station forms to suppress the interference.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service

Art Unit: 2618

area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claim 41, Takao et al discloses a computer readable program (figs. 1-3), that operably controls a radio base station (21 or 22 of figs. 1 and 3) in a radio communication system, said radio communication system including plural radio base stations each providing a service area and a radio resource management apparatus for managing radio resources of said radio base stations (col. 3, line 44- col. 4, line 16; col. 8, line 33), comprising the steps of: measuring (21 or 22 of figs. 1 and 3) a radio link quality and then notifying said radio resource management apparatus (12 of figs. 1 and 3) of radio link resource information being a measurement result (col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of responding to transmission power control produced from said radio resource management apparatus and thus controlling a change of transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference between service areas detected based on the measurement result in said radio resource management apparatus.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal

Art Unit: 2618

power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the

Art Unit: 2618

invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claim 42, Takao et al discloses a computer readable program (figs. 1-3), that computer controls the operation of a radio base station (21 or 22 of figs. 1 and 3) in a radio communication system, said radio communication system including plural radio base stations (21 or 22 of figs. 1 and 3) each providing a service area and a radio resource management apparatus for managing radio resources of said radio base stations (col. 3, line 44- col. 4, line 16; col. 8, line 33; 21 or 22 of figs. 1 and 3; col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of responding to occurrence of interference between plural service areas and controlling transmission power, to suppress interference autonomously.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and

Art Unit: 2618

performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and

Art Unit: 2618

Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claim 43, Takao et al discloses a computer readable program (figs. 1-3) for executing the operation of a radio terminal by means of a computer, comprising the control step of distributively controlling a load, being a radio terminal accommodated in a radio base station (col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of responding a control indication based on a radio link qualities notified from plural radio terminals, said radio link quality information including radio interference information.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Regarding claim 46, Takao et al discloses a computer readable program (figs. 1-3) for executing the operation of a radio terminal by means of a computer, comprising the steps of:

Art Unit: 2618

measuring a radio link quality and notifying a radio resource management apparatus (12 of figs. 1 and 3) of the radio link quality information being the measurement result (col. 9, line 42- col. 10, line 55; col. 11, line 65; col. 19, line 8- col. 20, line 45).

However, Takao et al does not specifically disclose the steps of responding a distributed control indication of a load based on a radio link quality information, said radio link quality information including radio interference information, said dispersion control being created from said radio resource management apparatus, said load being a radio terminal accommodated in a radio base station, and thus switching a radio base station to be connected.

On the other hand, Sawahashi et al, from the same field of endeavor, discloses a transmission power control method of a mobile station in a Code Division Multiple Access system which primarily controls transmission power of the mobile station by using a closed loop control which enables high accuracy power control (col. 5, lines 3-27). The base station measures a desired received power level, and calculates its signal to interference ratio. In addition, the base station estimates a transmission power at two transmission power control periods by comparing the measured signal to interference ratio with a predetermined reference signal to interference ratio (col. 5, line 62-col. 6, line 31; col. 7, lines 1-30). The desired signal power detector detects the power level of the intended received signal from the base station, and performs the calculations (col. 8, lines 1-31). It is considered that Sawahashi the steps of controlling transmission power of a common control signal, which governs a scope of service area that a radio base station forms, to suppress interference (col. 5, line 62-col. 6, line 31; col. 8, lines 1-16).

Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the modified system of Sawahashi and Takao in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Claim Rejections - 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in a patent granted on an application for patent by another filed in the United States before the invention thereof by the applicant for patent, or on an international application by another who has fulfilled the requirements of paragraphs (1), (2), and (4) of section 371(c) of this title before the invention thereof by the applicant for patent.

The changes made to 35 U.S.C. 102(e) by the American Inventors Protection Act of 1999 (AIPA) and the Intellectual Property and High Technology Technical Amendments Act of 2002 do not apply when the reference is a U.S. patent resulting directly or indirectly from an international application filed before November 29, 2000. Therefore, the prior art date of the reference is determined under 35 U.S.C. 102(e) prior to the amendment by the AIPA (pre-AIPA 35 U.S.C. 102(e)).

5. Claims 31, 38-40, 44-45 are rejected under 35 U.S.C. 102(e) as being anticipated by Partain et al (US Patent No 7068607 B2).

Regarding claim 31, Partain et al discloses a radio resource management apparatus (figs. 1-3) comprising: controller (RNC of fig. 6; the radio network controller is responsible for radio resource management for the UTRAN application) for controllably changing a frequency used by a radio base station based on information on radio link qualities notified from plural radio

Art Unit: 2618

terminals (fig. 1; col. 4, lines 9-20; col. 6, lines 1-33; col. 5, lines 23-36). Partain et al shows in figure 3, a bandwidth broker server that collects information from various load measurement proxies located at various points in the network. This information is used to determine the congestion state of various paths through the network (col. 6, lines 8-25). The bandwidth broker processes the on-demand admission requests for IP resources by using the results of load control measurements (abstract; col. 3, lines 46-65).

Regarding claim 38, Partain et al discloses a computer readable program, that operably controls a radio resource management apparatus in a radio communication system (figs. 1-3), comprising a control step of distributively controlling a load (RNC of fig. 6; the radio network controller is responsible for radio resource management for the UTRAN application), being a radio terminal accommodated by a radio base station based on information on radio link qualities notified from plural radio terminals (fig. 1; col. 4, lines 9-20; col. 6, lines 1-33; col. 5, lines 23-36). Partain et al shows in figure 3, a bandwidth broker server that collects information from various load measurement proxies located at various points in the network. This information is used to determine the congestion state of various paths through the network (col. 6, lines 8-25). The bandwidth broker processes the on-demand admission requests for IP resources by using the results of load control measurements (abstract; col. 3, lines 46-65).

Regarding claim 39, Partain et al discloses a computer readable program, that operably controls a radio resource management apparatus in a radio communication system (figs. 1-3), comprising a control step of distributively controlling a load (RNC of fig. 6; the radio network controller is responsible for radio resource management for the UTRAN application), being a radio terminal accommodated by a radio base station based on information on radio link qualities

Art Unit: 2618

notified from plural radio terminals (fig. 1; col. 4, lines 9-20; col. 6, lines 1-33; col. 5, lines 23-36). Partain et al shows in figure 3, a bandwidth broker server that collects information from various load measurement proxies located at various points in the network. This information is used to determine the congestion state of various paths through the network (col. 6, lines 8-25). The bandwidth broker processes the on-demand admission requests for IP resources by using the results of load control measurements (abstract; col. 3, lines 46-65).

Regarding claim 40, Partain et al discloses a computer readable program, that operably controls a radio resource management apparatus (figs. 1-3) in a radio communication system comprising a control step (RNC of fig. 6; the radio network controller is responsible for radio resource management for the UTRAN application) of controllably changing a frequency used by a radio base station (BTS of fig. 1) based on information on radio link qualities notified from plural radio terminals (fig. 1; col. 4, lines 9-20; col. 6, lines 1-33; col. 5, lines 23-36). Partain et al shows in figure 3, a bandwidth broker server that collects information from various load measurement proxies located at various points in the network. This information is used to determine the congestion state of various paths through the network (col. 6, lines 8-25). The bandwidth broker processes the on-demand admission requests for IP resources by using the results of load control measurements (abstract; col. 3, lines 46-65).

Regarding claim 44, Partain et al discloses a computer readable program for executing a radio resource management apparatus (figs. 1-3) in a radio communication system by means of a computer, comprising the control step (RNC of fig. 6; the radio network controller is responsible for radio resource management for the UTRAN application) of controlling transmission power of a radio base station (BTS of fig. 1) based on information on radio link qualities notified from

plural radio terminals (fig. 1; col. 4, lines 9-20; col. 6, lines 1-33; col. 5, lines 23-36). Partain et al shows in figure 3, a bandwidth broker server that collects information from various load measurement proxies located at various points in the network. This information is used to determine the congestion state of various paths through the network (col. 6, lines 8-25). The bandwidth broker processes the on-demand admission requests for IP resources by using the results of load control measurements (abstract; col. 3, lines 46-65).

Regarding claim 45, Partain et al discloses a computer readable program for executing a radio resource management apparatus (figs. 1-3) in a radio communication system, by means of a computer, comprising the control step (RNC of fig. 6; the radio network controller is responsible for radio resource management for the UTRAN application) of controllably changing a frequency used by a radio base station (BTS of fig. 1) based on information on radio link qualities notified from plural radio terminals (fig. 1; col. 4, lines 9-20; col. 6, lines 1-33; col. 5, lines 23-36). Partain et al shows in figure 3, a bandwidth broker server that collects information from various load measurement proxies located at various points in the network. This information is used to determine the congestion state of various paths through the network (col. 6, lines 8-25). The bandwidth broker processes the on-demand admission requests for IP resources by using the results of load control measurements (abstract; col. 3, lines 46-65).

Claim Rejections - 35 USC § 103

6. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject

matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

7. Claim 32 is rejected under 35 U.S.C. 103(a) as being unpatentable over Partain et al (US Patent No 7068607 B2) in view of Carlsson et al (US Patent No 6167240).

Partain et al discloses everything claimed as explained in claim 31, except the features a control means control means that controls the frequency of a radio base station based on an interference amount being an average value of reception levels from neighboring radio base stations of the same frequency as the frequency used by an interested radio base station.

However, Carlsson et al also discloses a system and a method to reduce interference in a cellular communication system including at least one controlling arrangement communicating with a number of base stations, each of which serves a cell, and a number of mobile stations controlled by the base stations. Each base station includes a detecting device for detecting interfering signals from one or more mobile stations controlled by other base stations. The base stations also include an alarm-activating device for activating the transmission of an alarm signal if interference is detected. The controlling arrangement includes a device for requesting identification of all mobile station in the neighborhood of the interfered base station. A device is also provided for establishing which controls base station an interfering mobile station, and the base station controlling the interfering mobile station takes the appropriate action to reduce the interference level (col. 2, lines 23-60; col. 4, lines 4-40). Furthermore, Carlsson et al shows in

Art Unit: 2618

figure 5, a detector is implemented called base station user detector and which is used for detecting the users. The interference detector detects interfering signals generated by mobile stations controlled by other base stations (col. 7, lines 16-57; fig. 10; col. 8, line 51- col. 9, line 11). It is clearly stated that the occurrence of interference is detected based on the radio link quality information notified from the base stations (col. 7, lines 28-49; col. 8, line 55- col. 9, line 11). Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to apply the technique of Carlsson to the communication system of Partrain in order to provide a detector device in a base station for the purpose of reducing interference in a cellular communication system.

Allowable Subject Matter

8. Claims 3, 6, 12-13, 15-16, 24-25, 30 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Marceau Milord whose telephone number is 571-272-7853. The examiner can normally be reached on Monday-Thursday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Matthew D. Anderson can be reached on 571-272-4177. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2618

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

MARCEAU MILORD

Marceau Milord

Primary Examiner

Art Unit 2618


MARCEAU MILORD
PRIMARY EXAMINER